

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | | |
|---|--|--|---|
| (51) International Patent Classification ⁷ : F41A 17/06 | | A1 | (11) International Publication Number: WO 00/65291 |
| | | | (43) International Publication Date: 2 November 2000 (02.11.00) |
| (21) International Application Number: PCT/EP00/01613 (22) International Filing Date: 26 February 2000 (26.02.00) (30) Priority Data: 99810350.1 26 April 1999 (26.04.99) EP (71) Applicant (for all designated States except US): LAQUILA SA [CH/CH]; Via Lucomagno, 10, CH-6710 Biasca (CH). (72) Inventor; and (75) Inventor/Applicant (for US only): HEFTI, Aldo [CH/CH]; Via Motta, 10, CH-6710 Biasca (CH). (74) Agent: AMMANN PATENT ATTORNEYS LTD. BERNE; Schwarztorstrasse 31, CH-3001 Berne (CH). | | (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. | |

(54) Title: FIRE WEAPON CONTROL SYSTEM INCLUDING SAFETY MEANS



(57) Abstract

A fire weapon control system including safety means for preventing firing of the weapon by an unauthorized user. The system comprises a weapon having a weapon control means including a reader (23) lodged in a hollow part of the weapon handle (24), said reader comprising a transceiver composed of signal transmitter means and signal receiver means, the output of the receiver means being used to control the position of the safety means (27). The system further comprises a user identification element (15) adapted to be worn by a user of the weapon, said element having a transponder (14) adapted to receive a signal from said transmitter means. The transponder (14) of the user identification element (15) is adapted to receive a signal from said transmitter means in the weapon and to generate a transponder signal back to the weapon. The receiver means in the weapon have a recognition means responsive to at least one coded identification carried by the transponder signal, and a means for generating an output signal to operate said safety means (27) for release of the safety means to the armed position.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | | | |
|----|--------------------------|----|--|----|--|----|--------------------------|
| AL | Albania | ES | Spain | LS | Lesotho | SI | Slovenia |
| AM | Armenia | FI | Finland | LT | Lithuania | SK | Slovakia |
| AT | Austria | FR | France | LU | Luxembourg | SN | Senegal |
| AU | Australia | GA | Gabon | LV | Latvia | SZ | Swaziland |
| AZ | Azerbaijan | GB | United Kingdom | MC | Monaco | TD | Chad |
| BA | Bosnia and Herzegovina | GE | Georgia | MD | Republic of Moldova | TG | Togo |
| BB | Barbados | GH | Ghana | MG | Madagascar | TJ | Tajikistan |
| BE | Belgium | GN | Guinea | MK | The former Yugoslav Republic of Macedonia | TM | Turkmenistan |
| BF | Burkina Faso | GR | Greece | | | TR | Turkey |
| BG | Bulgaria | HU | Hungary | ML | Mali | TT | Trinidad and Tobago |
| BJ | Benin | IE | Ireland | MN | Mongolia | UA | Ukraine |
| BR | Brazil | IL | Israel | MR | Mauritania | UG | Uganda |
| BY | Belarus | IS | Iceland | MW | Malawi | US | United States of America |
| CA | Canada | IT | Italy | MX | Mexico | UZ | Uzbekistan |
| CF | Central African Republic | JP | Japan | NE | Niger | VN | Viet Nam |
| CG | Congo | KE | Kenya | NL | Netherlands | YU | Yugoslavia |
| CH | Switzerland | KG | Kyrgyzstan | NO | Norway | ZW | Zimbabwe |
| CI | Côte d'Ivoire | KP | Democratic People's Republic of Korea | NZ | New Zealand | | |
| CM | Cameroon | | | PL | Poland | | |
| CN | China | KR | Republic of Korea | PT | Portugal | | |
| CU | Cuba | KZ | Kazakhstan | RO | Romania | | |
| CZ | Czech Republic | LC | Saint Lucia | RU | Russian Federation | | |
| DE | Germany | LJ | Liechtenstein | SD | Sudan | | |
| DK | Denmark | LK | Sri Lanka | SE | Sweden | | |
| EE | Estonia | LR | Liberia | SG | Singapore | | |

- 1 -

FIRE WEAPON CONTROL SYSTEM INCLUDING SAFETY MEANS

The invention concerns a fire weapon control system including safety means for preventing firing of the weapon
5 by an unauthorized user.

Prior art fire weapon control systems of this kind are described in U.S. Patent Specifications Nos. 5,461,812 and 4,488,370.

10

There is a need for improving such prior art control systems in particular by reducing their energy consumption, their size, their cost, and by increasing their reliability.

15 The aim of the invention is therefore to provide an improved fire weapon control system of the above-mentioned kind which operates with reduced energy consumption, which is smaller and cheaper than prior art systems, and which in addition is more reliable.

20

According to the invention this aim is attained with a fire weapon control system defined by claim 1.

Preferred embodiments of the invention are defined by the
25 subclaims.

The main advantages of a fire weapon control system according to the invention are that it has a lower energy consumption and can be made much smaller and cheaper than
30 prior art systems, and that in addition it is more reliable, even under extreme climatic conditions.

Preferred embodiments of the invention are described hereinafter more in detail with reference to the
35 accompanying drawings.

- 2 -

Fig. 1 shows an exploded view of handgun control system according to the invention.

- 5 Fig. 2 is a perspective view illustrating a typical use of a handgun control system shown by Fig. 1.

Fig. 3 is a schematic diagram of a prior art receiver circuit used for PSK or FSK demodulation.

10

Fig. 4 is a schematic diagram of a receiver circuit used for ASK demodulation used in a weapon control system according to the invention.

- 15 Fig. 5 is a schematic diagram of a prior art demodulator used for PSK or FSK demodulation in a receiver circuit of the type shown by Fig. 3.

Fig. 6 is a schematic diagram of demodulator used for ASK demodulation used in a receiver circuit of the type shown by Fig. 4.

20

In the embodiments described hereinafter the weapon is a handgun. Within the scope of the invention the weapon can be also any similar firearm, e.g. a rifle or a rapid firing assault weapon.

25

As shown by Fig. 1 a handgun control system according to the invention basically comprises handgun control means lodged in a hollow part of the handgun handle (as described in detail hereinafter) and a user identification element 15, which is an element external to the handgun.

30

- 3 -

The handgun control means include safety means 27 for preventing firing of the handgun and further comprises a reader 23 lodged in a hollow part of the handgun handle 24, e.g. behind a hand grip wall 25 of handle 24. Reader 23
5 comprises a transceiver composed of a signal transmitter and a signal receiver. The output signal of this receiver is used to control the position of said safety means 27. Reader 23 also comprises a microprocessor which coordinates the operation of the transceiver, the receiver and the safety
10 means. This microprocessor controls the position of the safety means in response to signals provided by the receiver part of the transceiver.

In a preferred embodiment the microprocessor manages a
15 plurality of data related to use of the handgun, e.g. the point of time at which the control system of the handgun is put into operation, the points of time at which the handgun is used, the number of projectiles present in the cartridge of the handgun, etc. This plurality of data is stored in
20 memory means included in the microprocessor.

The transceiver of reader 23 comprises an antenna 21 which is lodged in a side wall of the handle 24 of the handgun and on the side of the handle which is located at the shortest
25 distance from the trigger of the handgun. Antenna 21 is distanced from metallic parts of the handgun in order to protect the operation of the control system against noise signals and in order to improve the signal-to-noise ratio of the useful signals.

30

Antenna 21 is so oriented that the main lobe of the transmitting field is directed towards the trigger of the handgun. Therefore, the main lobe of the transmitting field is directed towards the normal position of the user

- 4 -

identification element 15, e.g. a finger ring carried by the user, when the handgun is properly hold by the user.

5 Safety means 27 have a normally disarmed position and an armed position and are adapted for being moved from the normally disarmed position to said armed position in response to a signal from the signal receiver.

10 If the weapon is a handgun the user identification element 15 is preferably a finger ring adapted to be worn by an authorized user of the handgun as shown by Fig. 2. Element 15 includes a transponder 14 mounted on ring 15 and adapted for receiving a signal from said transmitter in the handgun.

15 If the weapon is a rifle the user identification element 15 is preferably a bracelet.

20 The transmitter in the handgun is adapted to elicit a response from the transponder 14 of the user identification element 15.

25 Transponder 14 of the user identification element 15 is adapted to receive a signal from the transmitter in the handgun and to generate a transponder signal back to the handgun.

30 The receiver in the handgun comprises recognition means responsive to at least one coded identification carried by the transponder signal, and a means for generating an output signal to operate safety means 27 for release of the safety means to their armed position.

In a preferred embodiment the coded identification carried by the transponder signal has a hierarchical structure which

- 5 -

allows identification of a plurality of authorized users of the handgun.

The receiver in the handgun further comprises an amplitude shift keying demodulator for demodulating the transponder signal sent to the handgun.

A preferred embodiment of a handgun control system according to the invention further comprises programming means for coding said at least one identification in the transponder and in the recognition means of the receiver means in the handgun.

In a preferred embodiment, the handgun control system further comprises a switch 33 for connecting a power supply 29 to electric circuits of said control means of the handgun.

In a preferred embodiment, power supply 29 is normally disconnected from those electric circuits, and is adapted to be connected to those electric circuits by means of switch 33 when the user holds the handle of the handgun, or when pressure is applied to the trigger. Instead of switch 33 any other activation means having the function of a switch can be used.

In a preferred embodiment the handgun control system further comprises a LED display 26 which shows the user the status of the batteries and preferably also the status of the handgun control system as a whole.

In a further preferred embodiment the handgun control system further comprises a device 36 or 37 for manually putting the handgun control system out of operation. Both devices 36, 37 requires the presence of an authorized transponder to

- 6 -

operate. Device 36 requires also the presence of an authorized transponder to return to the safety condition. Device 37 is adapted to return to the safety condition without the presence of an authorized transponder.

5

Batteries 29 are used as power supply. This batteries are preferably placed in a space or container located under the cartridge of the handgun. The battery container may be also connected to the cartridge.

10

In a preferred embodiment, the shape of the cartridge holder is used as part of a mechanism for putting the handgun control system out of operation. This is achieved for example by configuring the control system in such a way that removal of the cartridge puts the control system out of operation. It is thereby prevented that any projectile remaining in the handgun may be fired.

The simplification of the electric circuits of the control means of the handgun can be appreciated by comparing the receiver circuit for Amplitude Shift Keying (ASK) used in a handgun control system according to the invention represented by Fig. 4 with a receiver circuit for PSK (Phase Shift Keying) or FSK (Frequency Shift Keying) represented by Fig. 3. As shown by the latter Figure such a receiver circuit comprises the following elements/blocks connected in series: antenna 51, duplex filter 52, amplifier 53, filter 54, demodulator 55, filter 56, amplifier 57, A/D-converter 58 and output lead 59, whereas the receiver circuit represented by Fig. 4 only comprises the following elements/blocks connected in series: antenna 61, demodulator 62, filter 63, amplifier 64, A/D-converter 65 and output lead 66.

30

- 7 -

A further simplification provided by the use of ASK according to the invention can be by comparing the structure of the demodulator 62 for Amplitude Shift Keying (ASK) shown by Fig. 6 with the structure of an FM demodulator shown by Fig. 5. As shown by the latter Figure such an FM demodulator comprises the following elements/blocks (some of them are complex circuits): an input lead 71; a PLL circuit comprising a phase detector 73, a low-pass filter 74 and a voltage controlled oscillator 75; a resistor 76, a capacitor 77 and an output lead 78, whereas the ASK demodulator 62 represented by Fig. 6 only comprises the following elements/blocks (all of which are passive components): an input lead 81, a diode 82, a capacitor 83, resistors 84, 85, a capacitor 86 and an output lead 87.

15

From the foregoing it is clear that use of ASK according to the invention provides a considerable reduction of the number of components and therefore also of the size of the electric circuits of the handgun control system. A higher degree of miniaturization is therefore possible. Moreover manufacturing and maintenance costs are also much lower than those of prior art systems.

20

Moreover use of ASK according to the invention provides a considerable reduction of the energy consumption of the transceiver of reader 23 of the handgun control system. The energy consumption of such a transceiver is about nine times lower than the one of prior art transceivers for a similar purpose.

30

In addition use of ASK according to the invention provides a stronger signal to the input of the receiver part of the transceiver of reader 23. Therefore, operation of the handgun control system according to the invention is more

- 8 -

reliable, even under noise conditions that would seriously affect the reliability of prior art systems.

In a preferred embodiment the handgun control system,
5 special screws 42, 43, 44, 45 which can only be removed with
special tools are used for mounting the various parts of the
control system in the handle of the handgun, in order to
protect it against misuse. As a further protection against
misuse, screws 42, which fix the control system to the
10 handgun, are positioned internally.

- - - - -

- 9 -

Claims

1. A fire weapon control system including safety means for preventing firing of the weapon by an unauthorized user,

5 comprising:

a weapon having a weapon control means including
a reader (23) lodged in a hollow part of the weapon
handle (24), said reader comprising a transceiver composed
of signal transmitter means and signal receiver means, the
10 output of the receiver means being used to control the
position of said safety means (27),

said safety means (27) having a normally disarmed
position and an armed position, and being adapted for being
moved from the normally disarmed position to said armed
15 position in response to a signal from the signal receiver
means;

a user identification element (15) adapted to be worn
by a user of the weapon, said element having a transponder
(14) adapted to receive a signal from said transmitter
20 means;

said transmitter means in the weapon being adapted to
elicit a response from the transponder (14) of the user
identification element (15);

said transponder (14) of the user identification
25 element (15) being adapted to receive a signal from said
transmitter means in the weapon and to generate a
transponder signal back to the weapon;

said receiver means in the weapon having a recognition
means responsive to at least one coded identification
30 carried by the transponder signal, and a means for
generating an output signal to operate said safety means
(27) for release of the safety means to the armed position;.

said receiver means in the weapon having an amplitude
shift keying demodulator (62) for demodulating the
35 transponder signal sent to the weapon.

- 10 -

2. A fire weapon control system according to claim 1 and further comprising programming means for coding said at least one identification in the transponder and in the recognition means of the receiver means in the weapon.
3. A fire weapon control system according to claim 1, wherein said transceiver of reader (23) comprises an antenna (21) which is lodged in a side wall of the handle of the weapon and on the side of the handle which is located at the shortest distance from the trigger of the weapon, said antenna being distanced from metallic parts of the weapon, and being so oriented that the main lobe of the transmitting field is directed towards the trigger of the weapon.
4. A fire weapon control system according to claim 1, wherein said weapon is a handgun and said user identification element (15) is a finger ring which is adapted to be worn by a user of the weapon and which carries said transponder (14).
5. A fire weapon control system according to claim 1, wherein said weapon is a rifle and said user identification element (15) is a bracelet which is adapted to be worn by a user of the weapon and which carries said transponder (14).
6. A fire weapon control system according to claim 1 and further comprising a switch (33) for connecting a power supply (29) to electric circuits of said control means of the weapon, said power supply being normally disconnected from said electric circuits, and said power supply being adapted to be connected to said electric circuits by means of switch (33) when the user holds the handle of the weapon.

- 11 -

7. A fire weapon control system according to claim 1 wherein said coded identification carried by the transponder signal has a hierarchical structure allowing identification of a plurality of authorized users of the weapon.

5

8. A fire weapon control system according to claim 1 wherein said reader 23 also comprises a microprocessor which coordinates the operation of the transceiver, the receiver and the safety means.

10

9. A fire weapon control system according to claim 8 wherein said microprocessor manages a plurality of data related to use of the weapon.

15

- - - - -




Fig. 1




Fig. 2




Fig. 3






Fig. 4

*Fig. 5**Fig. 6*

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 00/01613

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F41A17/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F41A

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|---|-----------------------|
| Y | US 5 461 812 A (E. BENNETT) 31 October 1995 (1995-10-31) cited in the application column 4, line 1-36 column 3, line 3-12 page 2, line 46-66; figures 1-4 | 1-9 |
| Y | US 5 712 630 A (OONO KOJI ET AL) 27 January 1998 (1998-01-27) column 1, line 5 -column 2, line 43; claim 1 | 1-9 |
| A | US 4 488 370 A (LEMELSON JEROME H) 18 December 1984 (1984-12-18) cited in the application column 1, line 30-42 column 2, line 33-60 column 3, line 4-41; figures 1-6 | 1-8 |
| -/- | | |

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

3 May 2000

Date of mailing of the international search report

15/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Van der Plas, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/01613

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|---|-----------------------|
| A | US 5 168 114 A (ENGET JEROME M) 1 December 1992 (1992-12-01) the whole document | 1-8 |
| A | EP 0 412 427 A (SIEMENS ELEMA AB ;SIEMENS AG (DE)) 13 February 1991 (1991-02-13) column 1, line 47 -column 2, line 27 | 1 |
| A | US 5 734 965 A (GRABOW WILHELM ET AL) 31 March 1998 (1998-03-31) column 1, line 40-50 column 2, line 32-47 | 1 |
| A | US 5 062 232 A (EPPLER LARRY D) 5 November 1991 (1991-11-05) | |
| A | US 5 016 376 A (PUGH KENNETH J) 21 May 1991 (1991-05-21) | |
| A | US 4 154 014 A (SMITH JOSEPH E) 15 May 1979 (1979-05-15) | |

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 00/01613

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---------------------|---|--|
| US 5461812 A | 31-10-1995 | NONE | |
| US 5712630 A | 27-01-1998 | JP 8237178 A JP 8094743 A DE 19526998 A GB 2291767 A, B | 13-09-1996 12-04-1996 01-02-1996 31-01-1996 |
| US 4488370 A | 18-12-1984 | US 4354189 A US 4453161 A | 12-10-1982 05-06-1984 |
| US 5168114 A | 01-12-1992 | NONE | |
| EP 0412427 A | 13-02-1991 | US 4947407 A AU 615872 B AU 5583890 A DE 69028889 D DE 69028889 T JP 3076346 A | 07-08-1990 10-10-1991 14-02-1991 21-11-1996 27-02-1997 02-04-1991 |
| US 5734965 A | 31-03-1998 | DE 4410896 A AT 170633 T CZ 9602580 A WO 9526511 A DE 59503434 D EP 0753159 A ES 2121359 T HU 76006 A PL 316381 A | 05-10-1995 15-09-1998 13-08-1997 05-10-1995 08-10-1998 15-01-1997 16-11-1998 30-06-1997 06-01-1997 |
| US 5062232 A | 05-11-1991 | NONE | |
| US 5016376 A | 21-05-1991 | US 5123193 A | 23-06-1992 |
| US 4154014 A | 15-05-1979 | NONE | |

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)